



Type of luminaire

| | |
|----------------------------------|---|
| Type of luminaire | Wall light, |
| Photometric body | Light discovered. |
| Characteristics of the luminaire | A ceiling fixture with contemporary design. |

General information

| | |
|---------------------------------|--|
| Materials | Base - powder painted aluminum cast. Front - hot-dip galvanized steel or aluminum cast powder painted. Lens - clear polycarbonate, UV stabilized. Silicone gasket. |
| Mounting method | Fixture mounting: 2 holes ø0.177 inches, spacing 3.54x6.30 inches. |
| Terminal | Connection terminals: max 3x0.001 in ² en Option to connect fixture in loop max 3x0.0009 in ² . Round cord diameter ø0.11...0.16 inch.en |
| Type of light source | Lamp E26 Replaceable light source by an end-user. |
| Net / gross weight of luminaire | 3,42lbs / 3,79 lbs |
| Box dimensions [inch] | 13,98 x 6,69 x 4,72 |
| Luminaire dimensions [inch] | 12,20 x 6,30 x 4,13 |

Technical data

| | |
|----------------------|--------------------------------|
| Luminaire wattage | LED max 9W |
| Ta Rated temperature | +77°F, up to +122°F on request |
| Ambient temperature | TA MAX=+149°F |

Accessories sold separately

| | |
|-----------|-------------------|
| 205ZX0010 | Concreting anchor |
|-----------|-------------------|

Spare parts

| | |
|----------|------------|
| 06860004 | Lampshade. |
| 08550009 | Gasket. |

Files to download

Manual

Indexes

| Index | Color | RAL |
|--------|---------------------|------|
| 862UBL | BLACK | 9005 |
| 862UGA | HOT-DIP GALVANIZING | - |