



## Type of luminaire

Photometric body	Two-sided diffused light
Characteristics of the luminaire	A fixture with a wide range of applications, including lighting: wall surfaces, facades, and other architectural concepts.

## General information

Materials	Powder painted aluminum cast. Lampshade - safety glass, transparent. Silicone gasket.
Mounting method	Fixture mounting: 2 holes ø5mm spaced 63x112mm. According to the enclosed installation instructions.
Terminal	Connection terminals: max 3x2.5mm <sup>2</sup> , Cable with round sheath diameter range ø7...10.5 mm.
Type of light source	LED module, DALI / TD electronic power supply Replaceable light source by a professional. Replaceable control gear by a professional.
Light control	Light control - DALI/TD system
Luminaire weight net / gross	0,85kg / 0,91kg
Box dimensions [cm]	16cm x 14cm x 5,5cm
Luminaire dimensions [cm]	13cm x 13cm x 5cm

## Technical data

Driver durability	100000h
Luminaire wattage	10,3W
Luminaire luminous flux	830lm
Efficiency of the luminaire	80,6lm/W
ULOR	0,92%
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Flicker of light (Pst LM)	≤1
Strobe effect (SVM)	≤0.4
Colour rendering index CRI	80
L70B50 [wg LM-80]	102 000h
Power Factor luminaire	PF>0.9
Ta Rated temperature	+25°C, up to +50°C on request
Ambient temperature	TA MAX=+65°C

This product contains light sources of energy efficiency class **A** / **E** EPREL

Inrush current	6.7A/2.4us
----------------	------------

Maximum number of luminaires of this type per MCB:

B 10A: 46, B 16A: 74, C 10A: 74, C 16A: 119

## Spare parts

ZN2466XX0009	Service set.
--------------	--------------

## Files to download

Photometric LDT files	Photometric IES files
Manual	

## Indexes

Index	Color	RAL
2466AL	ALUMINUM	9006
2466BL	BLACK	9005
2466CG	CEMENT GREY	7033
2466CB	COPPER BROWN	8004
2466CS	CORTEN STEEL	approx. 8011
2466GR	GRAPHITE	7016
2466GB	GRAY BEIGE	7006
2466WH	WHITE	9003