



Type of luminaire

Photometric body	Single-sided light facing down.
Characteristics of the luminaire	Luminaire with a contemporary design. For lighting gardens, private areas, and other architectural concepts

General information

Materials	Extruded aluminum profile, powder coated. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.
Mounting method	According to the attached assembly instructions Other accessories must be purchased separately
Terminal	Connection terminals: max 3x4mm ² Possibility to connect the luminaire in loops max 3x2.5mm ² Round insulated cable with a maximum diameter of ø12.5 mm
Type of light source	LED module, power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Net / gross weight of luminaire	21,3kg / 23,7kg
Box dimensions [cm]	232x44x38
Luminaire dimensions [cm]	118x24x263

Technical data

4 LED modules.	Cree DK200305 V3 JB2835 3V 3K (ⓘ Datasheet)
Driver	TCI Mini MD 12,5W 250mA code 127036 Triac (ⓘ Datasheet)
Light source wattage	21,2W
Luminaire wattage	25W
Lamp luminous flux	3976lm
Luminaire luminous flux	2433lm
Light source efficiency	187,5lm/W
Efficiency of the luminaire	97,3lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>102 000h
Power Factor luminaire	PF 0,95
Ta Rated temperature	+25°C
Max ambient temperature	+40°C

This product contains light sources of energy efficiency class  / ⓘ EPREL

Optionally, the luminaire is also available:

- In the safety class for KL II
 - For LED color 2700K [1/1]
 - For a different luminous flux value
 - Version with surge protection device (SPD)
 - For a different color of the luminaire (according to the RAL color palette)
 - For a different luminaire height
- Terms of sale and other information, after contact with the Norlys Sales Department

Inrush current	4A / 50μs
----------------	-----------

Accessories sold separately

3091GA0009	Concreting anchor (anchor L700mm)
------------	------------------------------------

Spare parts

ZS1000zx0009	Service set.
--------------	--------------

Files to download

Photometric LDT files	Photometric IES files
Manual	



Indexes

Index	Color	RAL
1000AL	ALUMINIUM	9006
1000B	BLACK	9005
1000GR	GRAPHITE	7016
1000W	WHITE	9003