

Type of luminaire



Type of luminaire	Pole luminaire
Photometric body	Ledil lens type SCL (very wide light distribution: type II / III)
Characteristics of the luminaire	Luminaire with a contemporary design. For lighting gardens, private areas, and other architectural concepts

General information

Materials	Extruded aluminum profile, powder coated. Lens - clear polycarbonate, UV stabilized.
Mounting method	According to the attached assembly instructions Other accessories must be purchased separately
Terminal	Connection terminals: max 5x4mm ² Possibility to connect the luminaire in loops max 5x2.5mm ² Round insulated cable with a maximum diameter of ø13.6 mm
Type of light source	LED module, DALI outdoor electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	System light control: DALI outdoor full programm. The power supply is programmed for the maximum permitted current. Programming of other parameters after contact with the Norlys Sales Department.
Net / gross weight of luminaire	21,3kg / 23,7kg
Box dimensions [cm]	44x38x232
Luminaire dimensions [cm]	118x24x263

Technical data

2 LED modules	Philips Fortimo FastFlex LED 2x6 DP G5 3K (⌘ Datasheet)
Driver	Philips Xi FP 40W 0.2-0.7A SNLDAE 230V S175 929002128306 (⌘ Datasheet)
Driver durability	100000h
External control	DALI2 (XI FP NLD) (User manual)
Light source wattage	13W
Luminaire wattage	16,3W
Lamp luminous flux	2317lm
Luminaire luminous flux	2216lm
Light source efficiency	178,2lm/W
Efficiency of the luminaire	136lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM5
Flicker of light (Pst LM)	≤0.1
Strobe effect (SVM)	≤0.1
Colour rendering index CRI	70
Rated life time L80/B20 at 25°C	>100 000h
Power Factor luminaire	PF 0,92
THD factor	7%
Overvoltage	6 / 10kV
Ta Rated temperature	+25°C
Max ambient temperature	-40...+35°C

This product contains light sources of energy efficiency class  /  EPREL

Optionally, the luminaire is also available:

- For special orders, other available operating modes/dimming as part of the "middle of the night" DALI outdoor system

AstroDim / Dynadimmer

- For a different luminous flux value

- Version with surge protection device (SPD)

- For a different color of the luminaire (according to the RAL color palette)

Terms of sale and other information, after contact with the Norlys Sales Department

Inrush current	21A / 225μs
----------------	-------------

Accessories sold separately

3091GA0009	Concreting anchor (anchor L700mm)
------------	------------------------------------

Spare parts

ZS1010zx0009	Service set.
--------------	--------------



Files to download

Photometric LDT files

Photometric IES files

Manual

Indexes

Index	Color	RAL
1010AL	ALUMINIUM	9006
1010B	BLACK	9005
1010GR	GRAPHITE	7016