



Type of luminaire

| | |
|----------------------------------|--------------------------------------|
| Photometric body | Single-sided light facing down. |
| Characteristics of the luminaire | Luminaire with a contemporary design |

General information

| | |
|---------------------------------|---|
| Materials | Extruded aluminum profile, powder coated. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. |
| Mounting method | According to the attached assembly instructions Other accessories must be purchased separately |
| Type of light source | LED module, power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional. |
| Light control | Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE) |
| Net / gross weight of luminaire | 21,3kg / 23,7kg |
| Box dimensions [cm] | 232x44x38 |
| Luminaire dimensions [cm] | 118x24x263 |

Technical data

| | |
|-------------------------------------|---|
| 4 LED modules. | Cree DK200305 V3 JB2835 3V 3K (ⓘ Datasheet) |
| Driver | TCI Mini MD 12,5W 250mA code 127036 Triac (ⓘ Datasheet) |
| Light source wattage | 21,2W |
| Luminaire wattage | 25W |
| Lamp luminous flux | 3976lm |
| Luminaire luminous flux | 2433lm |
| Light source efficiency | 187,5lm/W |
| Efficiency of the luminaire | 97,3lm/W |
| Color temperature | 3000K |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Colour rendering index CRI | 80 |
| Rated life time L70/B50 at 25°C | >72 000h |
| Ta Rated temperature | +25°C |
| Max ambient temperature | +40°C |

This product contains light sources of energy efficiency class **A** / **C** / **E** EPREL

Optionally, the luminaire is also available:

- In the safety class for KL II
 - For LED color 2700K [1/1]
 - For a different luminous flux value
 - Version with surge protection device (SPD)
 - For a different color of the luminaire (according to the RAL color palette)
 - For a different luminaire height
- Terms of sale and other information, after contact with the Norlys Sales Department

| | |
|----------------|-----------|
| Inrush current | 4A / 50μs |
|----------------|-----------|

Accessories sold separately

| | |
|------------|-------------------|
| 3091GA0009 | Concreting anchor |
|------------|-------------------|

Spare parts

| | |
|--------------|--------------|
| ZS1000zx0009 | Service set. |
|--------------|--------------|

Files to download

| | |
|-----------------------|-----------------------|
| Photometric LDT files | Photometric IES files |
| Manual | |

Indexes

| Index | Color | RAL |
|--------|-----------|------|
| 1000AL | ALUMINIUM | 9006 |
| 1000B | BLACK | 9005 |
| 1000GR | GRAPHITE | 7016 |