

Type of luminaire


Photometric body	Single-sided light facing down.
Characteristics of the luminaire	Luminaire with a contemporary design

General information

Materials	Extruded aluminum profile, powder coated. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.
Mounting method	According to the attached assembly instructions Other accessories must be purchased separately
Type of light source	LED module, power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Net / gross weight of luminaire	21,3kg / 23,7kg
Box dimensions [cm]	232x44x38
Luminaire dimensions [cm]	118x24x263

Technical data

4 LED modules.	Cree DK200305 V3 JB2835 3V 4K (ⓘ Datasheet)
Driver	TCI Mini MD 12,5W 250mA code 127036 Triac (ⓘ Datasheet)
Light source wattage	21,2W
Luminaire wattage	25W
Lamp luminous flux	4168lm
Luminaire luminous flux	2476,1lm
Light source efficiency	196,6lm/W
Efficiency of the luminaire	99lm/W
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>72 000h
Power Factor luminaire	PF 0,9
Ta Rated temperature	+25°C
Max ambient temperature	+40°C

This product contains light sources of energy efficiency class  / ⓘ EPREL

Optionally, the luminaire is also available:

- In the safety class for KL II
 - For LED color 2700K [1/1]
 - For a different luminous flux value
 - Version with surge protection device (SPD)
 - For a different color of the luminaire (according to the RAL color palette)
 - For a different luminaire height
- Terms of sale and other information, after contact with the Norlys Sales Department

Inrush current	4A / 50μs
----------------	-----------

Accessories sold separately

3091GA0009	Concreting anchor
------------	-------------------

Spare parts

ZS1001zx0009	Service set.
--------------	--------------

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1001AL	ALUMINIUM	9006
1001B	BLACK	9005
1001GR	GRAPHITE	7016