



Allmän information

Typ armatur	Takarmatur
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Klart polykarbonat, UV stabiliserat
Typ ljuskälla	LED module, DALI electronic power supply
Ljusstyrning	Light control - DALI system
Netto / Bruttovikt armatur	2,42kg / 2,72kg
Förpackning mått [cm]	23x22x13
Armaturens mått [cm]	20x20x11
LED	Philips Fortimo DLM Flex 5000/840 Gen2 4K (☞ Produktblad)
Drivdon	TCI Mini JOLLY 20W code 151403 BI DALI (☞ Produktblad)
Armatur effekt	19,1W
Lumen ut	2421lm
Armaturens effekt	126,8lm/W
Färgtemperatur	4000K
Färgbeständighet (McAdam ellipse)	SDCM3
Ljusflimmer (Pst LM)	≤1
Strobosc-effekt (SVM)	≤
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>100 000h
Nominell livstid L80/B20 vid 25°C	>100 000h
Energieffektivitetsindex (EEL)	A D / ☞ EPREL
Effektfaktor	0,96
THD-faktor	10%
Ta nominel:	+25°C
Maximal omgivningstemperatur	-20 ... +40°C
Inrush current	5A / 50μs

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer

