

Type of luminaire


Photometric body	Two-sided diffused light
Characteristics of the luminaire	Luminaire with a wide range of applications, including for the lighting of: wall surfaces, facades, and other architectural concepts.

General information

Materials	Powder painted aluminum cast. Lampshade - safety glass, transparent. Silicone gasket.
Mounting method	Luminaire mounting: 2 holes $\varnothing 5$ mm, 63x112mm spacing. According to the attached installation instructions.
Terminal	Connection terminals: max 3x2.5mm ² , \r\nCable in a round sheath with a diameter in the range of $\varnothing 7$...10.5 mm.
Type of light source	LED module, DALI / TD electronic power supply Replaceable light source by a professional. Replaceable control gear by a professional.
Light control	Light control - DALI/TD system
Luminaire weight net / gross	0,85kg / 0,91kg
Box dimensions [cm]	16cm x 14cm x 5,5cm
Luminaire dimensions [cm]	13cm x 13cm x 5cm

Technical data

Driver durability	100000h
Luminaire wattage	10,1W
Luminaire luminous flux	745lm
Efficiency of the luminaire	73,8lm/W
ULOR	0,92%
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM3
Flicker of light (Pst LM)	≤ 1
Strobe effect (SVM)	≤ 0.4
Colour rendering index CRI	80
L70B50 [wg LM-80]	102 000h
Power Factor luminaire	PF>0.9
Ta Rated temperature	+25°C, up to +50°C on request
Ambient temperature	TA MAX=+65°C

This product contains light sources of energy efficiency class  /  EPREL

Inrush current	6.7A/2.4us
----------------	------------

Maximum number of luminaires of this type per MCB:

B 10A: 46, B 16A: 74, C 10A: 74, C 16A: 119

Spare parts

ZN2465XX0009	Service set.
--------------	--------------

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
2465AL	ALUMINUM	9006
2465BL	BLACK	9005
2465CG	CEMENT GREY	7033
2465CB	COPPER BROWN	8004
2465CS	CORTEN STEEL	approx. 8011
2465GR	GRAPHITE	7016
2465GB	GRAY BEIGE	7006
2465WH	WHITE	9003