



Type of luminaire

Photometric body	Two-sided diffused light
Characteristics of the luminaire	A fixture with a wide range of applications, including lighting walls, facades, and other architectural concepts.

General information

Materials	Powder painted aluminum cast. Lampshade - safety glass, transparent. Silicone gasket.
Mounting method	Fixture attachment: 2 holes ø5mm spaced 63x112mm. According to the attached installation instructions.
Terminal	Connection terminals: max 3x2.5mm ² , possibility of looping the fixture max 3x1.5mm ² . Cable in a round sheath with diameter in the range ø7...10.5 mm.
Type of light source	LED module, electronic power supply Replaceable light source by a professional. Replaceable control gear by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Luminaire weight net / gross	0,85kg / 0,91kg
Box dimensions [cm]	16cm x 14cm x 5,5cm
Luminaire dimensions [cm]	13cm x 13cm x 5cm

Technical data

2 LED modules	Yes
Driver durability	50000h
Luminaire wattage	15W
Luminaire luminous flux	1079lm
Efficiency of the luminaire	71,9lm/W
ULOR	50%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Flicker of light (Pst LM)	≤1
Strobe effect (SVM)	≤0.4
Colour rendering index CRI	80
L70B50 [wg LM-80]	102 000h
Power Factor luminaire	PF>0.9
Ta Rated temperature	+25°C, up to +50°C on request
Ambient temperature	TA MAX=+65°C

This product contains light sources of energy efficiency class **A** / **EPREL**

Ability to adjust the fixture's power from 10.9W to 15W using a switch located on the power supply. Factory settings at 10.9W

Inrush current	10A/13.5us
----------------	------------

Spare parts

ZN2482XX0009	Service set.
--------------	--------------

Files to download

Photometric LDT files	Photometric IES files
Manual	



Indexes

Index	Color	RAL
2482AL	ALUMINUM	9006
2482BL	BLACK	9005
2482CG	CEMENT GREY	7033
2482CB	COPPER BROWN	8004
2482CS	CORTEN STEEL	approx. 8011
2482GR	GRAPHITE	7016
2482GB	GRAY BEIGE	7006
2482WH	WHITE	9003