



Type of luminaire

Photometric body Two-sided diffused light

Characteristics of the luminaire A fitting with a wide range of applications, including lighting: walls, facades, and other architectural concepts.

General information

Materials Powder painted aluminum cast. Lampshade - safety glass, transparent. Silicone gasket.

Mounting method Fitting attachment: 2 holes \varnothing 5mm spacing 63x112mm. As per the attached installation instructions.

Terminal Terminal connectors: max 3x2.5mm², possibility of looping the fitting max 3x1.5mm². Cable in a round sheath with a diameter within the range \varnothing 7...10.5 mm.

Type of light source LED module, electronic power supply Replaceable light source by a professional. Replaceable control gear by a professional.

Light control Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)

Luminaire weight net / gross 0,85kg / 0,91kg

Box dimensions [cm] 16cm x 14cm x 5,5cm

Luminaire dimensions [cm] 13cm x 13cm x 5cm

Technical data

2 LED modules Yes

Driver durability 50000h

Luminaire wattage 15W

Luminaire luminous flux 1043lm

Efficiency of the luminaire 69,5lm/W

ULOR 50%

Color temperature 2700K

Colour consistency (McAdam ellipse) SDCM3

Flicker of light (Pst LM) ≤ 1

Strobe effect (SVM) ≤ 0.4

Colour rendering index CRI 80

L70B50 [wg LM-80] 102 000h

Power Factor luminaire PF > 0.9

Ta Rated temperature +25°C, up to +50°C on request

Ambient temperature TA MAX = +65°C

This product contains light sources of energy efficiency class **A** / **c** / **EPREL**

Ability to adjust the lamp's power output from 10.9W to 15W using a switch located on the power supply. Factory settings: 10.9W

Inrush current 10A/13.5us

Maximum number of luminaires of this type per MCB:

B 10A: 37, B 16A: 60, C 10A: 62, C 16A: 102

Spare parts

ZN2483XX0009 Service set.

Files to download

Photometric LDT files

Photometric IES files

Manual



Indexes		
Index	Color	RAL
2483AL	ALUMINUM	9006
2483BL	BLACK	9005
2483CG	CEMENT GREY	7033
2483CB	COPPER BROWN	8004
2483CS	CORTEN STEEL	approx. 8011
2483GR	GRAPHITE	7016
2483GB	GRAY BEIGE	7006
2483WH	WHITE	9003